



### WORKGROUP COLOR DOCUMENT SYSTEMS



### A full-color ledger-size document system that will meet virtually all of your business needs.

Boost workgroup efficiency and productivity with Sharp's new MX-2616N/MX-3116N full color MULTI-FUNCTION DOCUMENT SYSTEMS, designed to deliver amazing image quality and consistent day-to-day performance while also being easy to afford. Features include STANDARD PCL®6 compatible printing language, a HIGH RESOLUTION TOUCH-SCREEN color display with graphical user navigation for easy operation, and a TOTAL PAPER CAPACITY UP TO 3,100 SHEETS. Equipped with a powerful TRUE MULTI-TASKING controller that allows quick processing of even complex print jobs, the MX-2616N/MX-3116N produces HIGH-QUALITY, vibrant color documents in-house, helping you save time and money. Sharp's advanced device management tools make it simple for businesses to control system access, color usage and costs. Sharp's industry-leading security helps assure the confidentiality of your intellectual property. That's the SHARP DIFFERENCE.

### High-Quality, Feature-Rich and a Strong Value.

- **True multi-tasking** full color document system
- **High-resolution 7" (diagonal) touch-screen** color display with graphical navigation
- Standard **PCL®6 compatible printing system** with available **PostScript®3** and compatible **XPS options\***
- **600 x 600 dpi** printing provides clear, crisp image output
- Advanced **ImageSEND™** function scans documents to USB devices, network folders, E-mail and more
- **ImageSEND** function scans documents at up to **50 images per minute** in both black and color
- Convenient **Document Filing System** with **thumbnail view** and **image preview** features
- Available **500 + 2,000 sheet tandem paper drawer**, for an online **capacity of 3,100 sheets\***
- **Flexible paper handling** system feeds up to 110 lb. index through paper trays and up to 140 lb. index through the bypass tray
- **Super G3 fax** option with intelligent inbound routing\*
- Supports Sharp's **award-winning** security platform with **standard 256-bit data encryption** and up to **7 times data overwrite protection**
- Convenient **end-of-lease feature** overwrites all job data, user data and network information at trade-in time
- **Remote front panel feature** allows users and administrators to view and control machine operations from a PC workstation
- **Environmentally-friendly design** offers low power consumption, fast warm up, compact design and long-life parts and supplies

\*Some features require optional equipment and/or software.

# MX-2616N/MX-3116N SPECIFICATIONS

## Main Specifications

|  |   |             |          |          |  |             |             |              |         |         |             |          |          |
|--|---|-------------|----------|----------|--|-------------|-------------|--------------|---------|---------|-------------|----------|----------|
| <b>MX-2616N</b>                              | Includes multi-tasking controller, 320 GB HDD with document filing system, PCL <sup>®</sup> 6 network printing, network scanning, 100-sheet RSPF, auto-duplex, one 500-sheet paper drawers and 100-sheet bypass. Black and color developer is included in the box.  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>MX-3116N</b>                              | Desktop, color multi-function digital document system   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Type</b>                                  | Desktop, color multi-function digital document system   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Display</b>                               | 7" (diagonally measured) color dot matrix touch panel. 800 x 480 dots (W-VGA)   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Functions</b>                             | Copy, print, network print, network scan, document filing and fax <sup>1</sup>  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Copy System</b>                           | Dry electrostatic transfer/Dual component developer/Magnetic brush development/OPC drums/Belt type fusing/white LED exposure  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Originals</b>                             | Sheets and bound documents  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Max Original Size</b>                     | 11" x 17"   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Copy Size</b>                             | Min. 5½" x 8½", Max. 11" x 17" + 12" x 18"  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Copy Speed</b>                            | 26/31 ppm B&W/Color (8½" x 11")   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Multiple Copy</b>                         | Max. 999 copies   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>First Copy Time (Seconds)<sup>2</sup></b> | <table border="1"> <tr> <td></td> <td>MX-2616N</td> <td>MX-3116N</td> </tr> <tr> <td></td> <td>Black Color</td> <td>Black Color</td> </tr> <tr> <td>Platen Glass</td> <td>5.9 8.1</td> <td>5.8 7.9</td> </tr> <tr> <td>Doc. Feeder</td> <td>9.1 11.6</td> <td>9.1 11.6</td> </tr> </table>  |             | MX-2616N | MX-3116N |  | Black Color | Black Color | Platen Glass | 5.9 8.1 | 5.8 7.9 | Doc. Feeder | 9.1 11.6 | 9.1 11.6 |
|  | MX-2616N  | MX-3116N    |          |          |  |             |             |              |         |         |             |          |          |
|  | Black Color   | Black Color |          |          |  |             |             |              |         |         |             |          |          |
| Platen Glass                                 | 5.9 8.1   | 5.8 7.9     |          |          |  |             |             |              |         |         |             |          |          |
| Doc. Feeder                                  | 9.1 11.6  | 9.1 11.6    |          |          |  |             |             |              |         |         |             |          |          |
| <b>Warm Up Time</b>                          | 18 seconds or less <sup>2</sup>   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Magnification</b>                         | 25% to 400% in 1% increments (with document feeder 25%-200%)  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Original Feed</b>                         | 100-sheet RSPF with original size detection   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Scan Speed</b>                            | Copy mode: Up to 50 opm (B&W) @ 600 x 400 dpi; Up to 36 opm (Color) @ 600 x 600 dpi.<br>Network Scan: Up to 50 opm (B&W or Color) 200 x 200 dpi. All times based on single-side letter originals.   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Original Sizes</b>                        | 5½" x 8½", 8½" x 11", 8½" x 11" R, 8½" x 14", 11" x 17" (13-32 lb. bond)  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Paper Capacity</b>                        | Std. 600 sheets / Max. 3,100 sheets   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Paper Feed System</b>                     | Standard: (1) 500-sheet paper drawer (letter/legal/ledger/statement size) and 100-sheet bypass tray (letter/legal/ledger/statement/envelope size). Optional: Single, double or triple drawer paper deck (500-sheets each drawer), tandem paper deck (500 + 2,000-sheets), letter/legal/ledger/statement size. See your local dealer for configurations.   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Paper Types</b>                           | Paper drawers: 16 lb. bond -110 lb. index. Other paper types include plain, pre-printed, recycled, pre-punched, letterhead and color paper. Bypass Tray: 16-28 lb. bond (plain paper), 13-16 lb. bond (thin paper), 28 lb. bond-140 lb. index (heavy paper), 20-24 lb. bond (Monarch/Com-10 envelope), tab paper (letter size only). Also label paper, gloss paper, pre-printed, recycled, pre-punched, letterhead, color paper and OHP film.   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Duplexing</b>                             | Standard automatic duplex copying and printing  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>CPU</b>                                   | Multi-processor controller  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Interface</b>                             | RJ-45 Ethernet (10/100/1000Base-T), USB 2.0 (2 host ports, front and rear), USB 2.0 (1 device ports)  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Memory</b>                                | Standard 3 GB + 2 GB option <sup>1</sup>  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Hard Disk Drive</b>                       | 320 GB  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Copy Resolution</b>                       | Scan: B&W/color: 600 dpi; Copy Output: B&W/color: 600 dpi   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Color Modes</b>                           | Auto Color Control (ACS), Full Color Mode, Monochrome (B/W)   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Exposure Control</b>                      | Modes: Automatic Text, Text/Photo, Text/Printed-Photo, Printed-Photo, Photo, Map, Pale-Color Document. Settings: Auto exposure control or 9 step manual exposure.   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Halftone</b>                              | 256 gradations/2 levels (monochrome)  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Copy Features</b>                         | Scan-Once Print-Many, electronic sorting, offset-stacking, Auto Color Sensing (ACS), Auto Paper Sensing (APS), Auto Magnification Sensing (AMS), auto tray switching, rotation copy, reserve copy, tandem copy, book copy, margin shift, tab-paper insertion, edge erase, center erase, dual page copy, cover pages, insert pages, OHP insertion, job build, card shot, multi-page enlargement, mirror image, black-white reversal, centering, proof copy, 2-in-1/4-in-1, pamphlet, photo repeat, document filing, account management, job programs, date/character/page stamp. |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Account Control</b>                       | Up to 1000 users. Supports user-number authentication (on device), login name/password (on device) or login name/password (on device via LDAP server) for Copy, Print, Scan, Fax and document management.   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Output Tray Capacity</b>                  | Main output tray (top) 400 sheets (face down); optional eject tray (right 1 side) 100 sheets (face down)  |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Firmware Management</b>                   | Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Management)   |             |          |          |  |             |             |              |         |         |             |          |          |
| <b>Configuration Method</b>                  | Web-based management with user/administrator level login, cloning (1 to N) with SRDM and remote front panel access  |             |          |          |  |             |             |              |         |         |             |          |          |

## Main Specifications (continued)

|                                   |   |
|-----------------------------------|---|
| <b>Service/Maintenance</b>        | Remote front panel access, remote access to service logs and click counts   |
| <b>Accessibility</b>              | Adjustment of Key Touch-Send and Speed, Concave Key, Document Feeder Free Stop, Job Programs, Remote Front Panel, Universal Grip for Paper Trays and Disable Screen Timeout   |
| <b>Environmental Standards</b>    | The International Energy Star Program (EPA) Ver. 1.2, Law on Promoting Green Purchasing <sup>®</sup> , European RoHS (Restriction of Hazardous Substances)  |
| <b>Power</b>                      | AC 100-127 VAC, 60 Hz, 12 Amps  |
| <b>Power Cons.</b>                | Maximum: 1440 W   |
| <b>Weight</b>                     | Approx. 166.7 lbs. (base model)   |
| <b>Dimensions</b>                 | 24" (w) x 25½" (d), x 33" (h)   |
| <b>Network Printing System</b>    |   |
| <b>PDL</b>                        | Standard PCL6 compatible, optional PostScript <sup>®</sup> 3 <sup>TM</sup> compatible, optional XPS   |
| <b>Resolution</b>                 | 600 x 600 dpi   |
| <b>Print Speed</b>                | 26/31 pages per minute (8½" x 11")  |
| <b>Print Drivers</b>              | Windows Server <sup>®</sup> 2003-2012, Windows <sup>®</sup> XP, Windows XP x64, Windows Server x64, Windows Vista <sup>®</sup> , Windows Vista <sup>®</sup> x64, Windows <sup>®</sup> 8, MAC OS <sup>®</sup> , OSX (including 10.4, 10.5-10.6, 10.7-10.8), all MAC PPD  |
| <b>Features</b>                   | Auto configuration, continuous printing, electronic sorting, offset stacking, N-up printing, duplex printing, transparency inserts, margin shift, image rotation, different cover page, poster print, job bypass print, job retention, confidential print, proof print, user authentication, image stamp and watermarks, multiple pamphlet, network tandem print, carbon copy print mode, different cover page/last page/other page, form overlay, tab paper settings, tab printing, chapter inserts, page interleave and bar code font printing (requires MX-PF10 bar code font kit) |
| <b>Direct Printing (optional)</b> | File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, Postscript and XPS <sup>1</sup> Methods: FTP, Web page, E-mail and USB memory  |
| <b>Resident Fonts</b>             | 80 outline fonts (PCL), 136 fonts (PS)  |
| <b>Interface</b>                  | RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0  |
| <b>Operating Systems</b>          | Windows Server 2003-2008, Windows XP, Windows Vista, Windows 7, MAC OS X 10.4.11, 10.5-10.5.8, 10.6-10.6.8, 10.7-10.7.4 Novell <sup>®</sup> Netware <sup>®</sup> 3x, 4x, 5x, Sun <sup>®</sup> OS 4.1x, Solaris <sup>®</sup> 2x, Unix <sup>®</sup> , Linux <sup>®</sup> and Citrix <sup>®</sup> (Metaframe, Presentation Server 4, 4.5) and Windows Terminal Services. <sup>1</sup>  |
| <b>Network Protocols</b>          | TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, 802.1x for Windows and Unix. LPD and LPR for UNIX. IPX/SPX <sup>®</sup> for Novell environments. EtherTalk <sup>®</sup> , AppleTalk <sup>®</sup> for Macintosh <sup>®</sup> environments. <sup>1</sup>   |
| <b>Printing Protocols</b>         | LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP and Novell Pserver/Rprinter   |
| <b>Network Security</b>           | IP/Mac address filtering, protocol filtering, port management, user authentication and document administration. <sup>1</sup>  |
| <b>Security Standards</b>         | IEEE-2600 <sup>TM</sup> 2008 for MFP devices, DoD (NSTISSP) #11, DoD Directive 8500.2, DoD (DISA) <sup>1</sup>  |
| <b>Network Scanning System</b>    |   |
| <b>Scan Modes</b>                 | Standard: Color, monochrome, grayscale  |
| <b>Max Original Size</b>          | 11" x 17"   |
| <b>Optical Resolution</b>         | 600 dpi   |
| <b>Output Modes</b>               | 600 dpi, 400 dpi, 300 dpi, 200 dpi, 100 dpi   |
| <b>Image Formats</b>              | Monochrome: TIFF, PDF, PDF/A, Encrypted PDF, XPS<br>Color: Grayscale, Color TIFF, JPEG, PDF, PDF/A, Encrypted PDF, XPS Internet Fax: TIFF-FX, FIFF-F, TIFF-S <sup>1</sup>   |
| <b>Image Compression</b>          | Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR)<br>Color/Grayscale: JPEG (high, middle, low)<br>Internet Fax mode: MH/MMR (option)  |
| <b>Scan Destinations</b>          | E-mail, Desktop, FTP, Folder (SMB), USB, Internet fax (option), Super G3 fax (option)   |
| <b>One-touch Destinations</b>     | Up to 1000 (combined scan destinations)   |
| <b>Group Dest.</b>                | Up to 500   |
| <b>Programs</b>                   | 48 (combined)   |
| <b>Max. Jobs</b>                  | Up to 94  |
| <b>Network Protocols</b>          | TCP/IP and SSL (includes HTTP, SMTP, LDAP, FTP, POP3), SMB, ESMTP and 802.1x.   |
| <b>Network Security</b>           | E-mail server user authentication for LDAP and Active Directory   |
| <b>Software</b>                   | Sharpdesk <sup>®</sup> desktop document management software (1 user license)  |

## B&W Super G3 Fax Kit (option)

|                                 |   |
|---------------------------------|---|
| <b>Transmission Mode</b>        | Super G3, G3  |
| <b>Modem Speed</b>              | 33.6 KBPS <sup>3</sup>  |
| <b>Compression Methods</b>      | JBIG, MMR, MR, MH   |
| <b>Scanning Method</b>          | Sheet fed simplex or duplex or book   |
| <b>Max. Transmit Resolution</b> | 400 dpi   |
| <b>Transmit Speed</b>           | Approx. 2 seconds with Super G3/JBIG <sup>4</sup>   |
| <b>Auto Dialing</b>             | Up to 1000 (combined scan destinations)   |
| <b>Group Dial/Destinations</b>  | Up to 500   |
| <b>Inbound Fax Long Length</b>  | Routing: Forwards received fax data to E-mail<br>Up to 31½" (for transmission)  |
| <b>Originals Programs</b>       | 48 (combined)   |
| <b>Memory</b>                   | 1 GB (shared)   |
| <b>Halftone</b>                 | 256 levels  |
| <b>Features</b>                 | Quick on-line transmission, direct transmission, F-Code transmission/reception, rotate transmission, in-bound fax routing, anti-junk fax reception, automatically staple received faxes, secure fax release, out of paper memory reception, auto redial, 2-in-1 reception, duplex reception transaction reports, activity reports and PC fax. |

## Inner Finisher (option)

|                           |  |
|---------------------------|--|
| <b>Type</b>               | Built-in finisher (hole-punch unit option)   |
| <b>Output Capacity</b>    | 500 sheets (letter/statement) or 250 sheets (ledger/legal size)  |
| <b>Output Delivery</b>    | Face down  |
| <b>Stapling Media</b>     | Plain paper, (letter, legal, or ledger size)   |
| <b>Stapling Positions</b> | 1 front, 1 rear, or both   |
| <b>Power Source</b>       | Supplied from main unit  |
| <b>Stapling</b>           | Up to 50 sheets (letter size) or 30 sheets (legal, ledger or mixed)                                    |
| <b>Stapled Sets</b>       | 30 bundles or 500 sheets (letter or statement size) or 30 bundles or 250 sheets (legal or ledger size) |
| <b>Hole Punching</b>      | Optional hole punch unit MX-PN11B (2 holes/3 holes)  |
| <b>Weight</b>             | Approx. 26.5 lbs.  |
| <b>Dimensions</b>         | 24¾" (w) x 23½" (d) x 8" (h) (includes extended tray)  |

## Optional Equipment

|                 |   |
|-----------------|---|
| <b>MX-DE12</b>  | Stand/1 x 500 Sheet Paper Drawer            |
| <b>MX-DE13</b>  | Stand/2 x 500 Sheet Paper Drawer            |
| <b>MX-DE14</b>  | Stand/3 x 500 Sheet Paper Drawer            |
| <b>MX-DE20</b>  | Stand/500 + 2,000 Sheet Tandem Paper Drawer |
| <b>MX-LT10</b>  | Long Paper Feeding Tray                     |
| <b>MX-36ABD</b> | Rolling Cabinet Base                        |
| <b>MX-FN17</b>  | Finisher                                    |
| <b>MX-PN11B</b> | 3 Hole Punch Unit (Requires MX-FN17)        |
| <b>MX-TR13N</b> | Exit Tray Unit                              |
| <b>MX-PK11</b>  | PostScript 3 Kit                            |
| <b>MX-PUX1</b>  | XPS Expansion Kit                           |
| <b>MX-FX11</b>  | Fax Expansion Kit                           |
| <b>MX-FWX1</b>  | Internet Fax Kit                            |
| <b>MX-PF10</b>  | Bar Code Font Kit                           |
| <b>MX-AMX1</b>  | Application Integration Module              |

## Supplies

|                  |                               |
|------------------|-------------------------------|
| <b>MX-23NTBA</b> | Black Toner Cartridge         |
| <b>MX-23NTCA</b> | Cyan Toner Cartridge          |
| <b>MX-23NTMA</b> | Magenta Toner Cartridge       |
| <b>MX-23NTYA</b> | Yellow Toner Cartridge        |
| <b>MX-36NVBA</b> | Black Developer               |
| <b>MX-36NVSA</b> | Cyan/Magenta/Yellow Developer |
| <b>MX-36NRSA</b> | Drum                          |
| <b>MX-230HB</b>  | Toner Collection Container    |

<sup>1</sup> Some features may require optional equipment and/or software.

<sup>2</sup> May vary depending on product configuration, machine settings and operating and/or environmental conditions.

<sup>3</sup> Actual transmission time will vary based on line conditions.

<sup>4</sup> Based on Sharp Standard Test Chart with approximately 700 characters, letter size in standard resolution.



SHARP ELECTRONICS CORPORATION  
Sharp Plaza, Mahwah, NJ 07495-1163  
1-800-BE-SHARP • www.sharpsusa.com

Design and specifications subject to change without notice. Sharp, Sharpdesk, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Windows, Windows Server and Windows Vista are trademarks or registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.

