ProJet® 1200

BOSYSTEMS

Micro-SLA Desktop 3D Printer



Print precise, small-scale prototypes and casting patterns at your desk with micro-SLA

The affordable ProJet® 1200 3D printer from 3D Systems provides the high precision and exceptionally fine feature detail of a professional 3D printer for an MSRP of \$4,900. It's perfect for producing strong, precise plastic prototypes of small mechanical components and other products right on your desk. You can even create metal parts by printing sacrificial patterns using the ProJet 1200's cast-ready materials.

Insert your choice of VisiJet® FTX material cartridges and get creative. FTX Gray parts are a primer-gray color ideal for painting. FTX Clear is a transparent material perfect for prototypes. FTX Cast and FTX Green are castable materials with clean, ash-free burnout. You can even print in sparkly materials with gold and silver metallic appearance.

The ProJet 1200 is compact and easy to use; everything you need is built right into the printer, including the part curing station.

The self-contained VisiJet FTX cartridges mean you don't have to measure and pour materials into the printer.

Convenient, simple and affordable, the ProJet 1200 belongs on your desk.

www.3dsystems.com

ProJet® 1200



Micro-SLA Desktop 3D Printer

Net Build Volume (xyz)	1.69 x 1.06 x 5.90 in (43 x 27 x 150 mm)				
Native Resolution (xy)	56 micron (effective 585 dpi*)				
Layer Thickness	0.0012 in (0.03 mm)				
Vertical Build Speed	Up to 0.55 in/hour (14 mm/hour)				
Material	VisiJet® FTX Green, FTX Cast, FTX Gray, FTX Clear, FTX Silver, FTX Gold				
Material Packaging	All-in-one cartridge with built-in print window				
Post-processing	Built-in UV Curing Station				
3DSPRINT Software	Easy, fast print prep and support generation				
PC requirements	Windows® 7 or 8, 64 bit				
	2.0 GHz Intel or AMD CPU, 3.0 GHz recommended				
	4 GB RAM minimum, 8 GB recommended				
	OpenGL 2.1 and GLSL 1.20 enabled graphics card				
	1280 x 960 or higher resolution				
	30 GB available HDD space for cache				
File Input	STL				
Electrical					
Input	100-240 VAC, 50/60 Hz, 2.0 A				
Output	24 V DC, 3.75 A, 90 W max				
Dimensions (WxDxH)					
3D Printer Crated	15 x 15 x 22 in (381 x 381 x 560 mm)				
3D Printer Uncrated	9 x 9 x 14 in (230 x 230 x 362 mm)				
Weight					
3D Printer Crated	25 lbs (12 kg)				
3D Printer Uncrated	20 lbs (9 kg)				

^{*} Enhanced LED DLP technology provides an effective resolution of 585 DPI.

3D Systems Corporation

moreinfo@3dsystems.com

Rock Hill, SC 29730

Tel: +1 803.326.3900

333 Three D Systems Circle

A low cost, professional-grade 3D printer

- Maximize your dollar The ProJet 1200 achieves unmatched part accuracy and surface finish for the most intricate parts and casting patterns.
- Make precise parts 585 dpi print resolution means you see every detail of your creations.
- Accelerate your workflow Fast print times mean you can go from design to part in just a few hours.
- Get started with 3D printing at a low price The ProJet 1200's affordability and its inexpensive prints make it the perfect tool.
 Print a ring for less than \$1 in materials.
- **Get started quickly** The ProJet 1200 features a convenient size and push-button operation.

Features:

- Enhanced LED DLP technology for 585 dpi resolution and 0.03 mm layers
- VisiJet FTX Cast material cleanly burns out for ash-free castings
- VisiJet FTX Gray shows off every detail and is ready for painting
- VisiJet FTX Clear creates models with a crystal-like appearance
- VisiJet FTX Gold and FTX Silver provide metallic appearance
- Integrated material cartridges ensure consistent high-quality parts every time
- · Factory calibrated for reliably accurate operation
- Network-ready and USB printing

Color Da		Wax and plastic hybrid for delicate castings Light green	Primer gray general purpose	Transparent Tough	Metallic silver appearance	Metallic gold appearance
	Oark Green	Liaht areen	C	-		
Cartridge Quantity 30			Gray	Clear	Silver	Gold
	0 g	30 g	30 g	30 g	30 g	30 g
Density @ 25° C (liquid) 1.0	.04 g/cm ³	1.01 g/cm ³	1.12 g/cm ³	1.1 g/cm ³	1.16 g/cm ³	1.16 g/cm ³
Tensile Strength ASTM D638 30	0 MPa	2.2 MPa	28 MPa	24 MPa	16 MPa	16 MPa
Tensile Modulus ASTM D638 17	700 MPa	154 MPa	1288 MPa	1075 MPa	701 MPa	866 MPa
Elongation at Break ASTM D638 10	0 %	2.20 %	6.20 %	13.50 %	11.70 %	5.70 %
Flexural Strength ASTM D638 40	0 MPa	3 MPa	38 MPa	31 MPa	22 MPa	18 MPa
Ash Content 0.0	.01 %	0.008 %	N/A	N/A	N/A	N/A



Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.